

Size	Resolution	Technologie	NTSC	OP Temp.	Brightness (cd/m ²)	Interface
4.3"	480x272	TN	50%	-20~70°C	500	TTL
5.0"	800x480	TN	50%	-20~70°C	500	TTL
5.0"	800x480	TN	50%	-20~70°C	350	TTL
5.0"	800x480	HFFS	70%	-40~85°C	1200	LVDS
5.7"	640x480	TN	50%	-30~85°C	220	TTL
7.0"	800x480	TN	45%	-30~85°C	500	TTL
7.0"	800x480	TN	50%	-30~85°C	450	TTL
7.0"	800x480	TN	50%	-20~70°C	450	TTL
7.0"	800x480	TN	50%	-20~70°C	680	TTL
7.0"	800x480	HFFS	70%	-20~70°C	600	LVDS
7.0"	800x480	HFFS	70%	-20~70°C	600	TTL
7.0"	1024x600	TN	50%	-20~70°C	500	LVDS
7.0"	1024x600	HFFS	50%	-20~70°C	600	LVDS
7.0"	800x1280	HFFS	60%	-20~70°C	450	LVDS
8.0"	800x480	TN	50%	-20~70°C	450	TTL
8.0"	800x480	TN	50%	-30~85°C	600	TTL
8.0"	1024x600	TN	50%	-20~70°C	600	LVDS
8.0"	1280x720	HFFS	70%	-30~85°C	600	LVDS
8.0"	800x1280	HFFS	58%	-20~60°C	350	MIPI
8.6"	400x1280	TN	70%	-30~85°C	1200	LVDS
8.8"	1280x480	HFFS	70%	-20~70°C	500	LVDS
9.0"	1024x600	TN	50%	-20~70°C	500	LVDS
9.0"	1280x720	HFFS	70%	-20~70°C	500	LVDS
10.1"	1024x600	TN	50%	-20~70°C	500	LVDS
10.1"	1280x600	TN	50%	-20~70°C	450	LVDS
10.1"	1280x800	HFFS	50%	-20~70°C	500	LVDS
10.1"	1280x720	HFFS	70%	-20~70°C	550	LVDS
10.1"	1920x1200	HFFS	50%	-20~50°C	700	LVDS
10.1"	1920x1200	HFFS	50%	0~60°C	400	eDP
10.1"	1920x1200	HFFS	50%	0~60°C	1200	eDP
10.1"	1920x1200	HFFS	50%	-20~70°C	700	LVDS
10.2"	1024x600	TN	70%	-20~70°C	400	LVDS
10.25"	1920x720	HFFS	70%	-30~85°C	840	LVDS
10.3"	1280x480	HFFS	70%	-20~70°C	800	LVDS
10.4"	640x480	TN	47%	-20~70°C	450	LVDS
10.4"	1024x768	TN	47%	-20~70°C	400	LVDS
10.4"	960x1280	HFFS	70%	-30~85°C	800	LVDS
11.4"	1024x600	TN	50%	-20~70°C	500	LVDS
12.1"	800x600	TN	60%	-30~80°C	450	LVDS
12.1"	1024x768	TN	70%	-20~70°C	600	LVDS
12.1"	1024x768	TN	70%	-30~80°C	600	LVDS
12.3"	1920x720	HFFS	70%	-30~85°C	800	LVDS
12.8"	1920x1080	HFFS	70%	-30~85°C	700	LVDS
13.6" Bar-type	1280x248	TN	72%	-20~70°C	450	LVDS
15.0"	1024x768	TN	60%	-30~80°C	450	LVDS
15.1" Bar-type	1280x248	TN	72%	-30~80°C	450	LVDS
15.6"	1920x1080	HFFS	70%	-30~85°C	850	LVDS
17.0"	1280x1024	TN	72%	-20~70°C	450	LVDS
19.0"	1280x1024	TN	72%	-30~80°C	450	LVDS
27.2" Bar-type	1920x145	HFFS	70%	-20~70°C	1000	LVDS
27.6"	1920x360	HFFS	70%	-20~70°C	1000	LVDS

Geplant

HFFS = High performance Field Fringe Switching